

RuralECO WPS412, 400V



Advantages



- Highest efficiency
- Latest control technology
- Internet Inside
- Photovoltaic Integration
- extremely maintenance free
- Smart Home Integration

General Data		
Power Range	B0/W35: 3 - 11	[kW]
Energy class VL 35°C	A+++	[-]
Energy class VL 55°C	A+++	[-]
Max. Flow temperature	62,0	[°C]
Electrical Data		
International Protection Marking	IP 20	[-]
Supply control	1/N/PE, 230V, 50Hz	[V, Hz]
Rated Input control	28	[W]
Cos(φ) control	0,90	[-]
Fuse control	1x B13	[-]
Supply compressor	3/N/PE, 400V, 50Hz	[V, Hz]
Operating current compressor	1,81	[A]
Starting current compressor	9 / -	[A / A]
Cos(φ) compressor	0,97	[-]
Fuse compressor	3x C16	[-]
Res. current circuit breaker comp. supply	30mA, Typ B or B+	[-]
Sound power level Data acc. EN12102		
Nom. Sound power level heat pump	44	[dB(A)]
Max. Sound power level heat pump	53	[dB(A)]
Level surcharge low-freq. noise characteristics	-	[dB]
Refrigerant circuit Data		
Compressor - Type	Scroll	[-]
Refrigerant - Type	R410a	[-]
Refrigerant - Amount	4	[kg]
Refrigerant - Fluid Group	2	[-]
Refrigerant - GWP	1924	[-]
Compressor Oil - Type	3MA-POE	[-]
Compressor Oil - Amount	1,18	[l]
Heating Side		
Condenser - Type	Plate heat exchanger	[-]
Condenser - Material	Stainless steel, copper brazed	[-]
Condenser - Flowrate (5K)	1,8	[m³/h]
Condenser pressure loss	4,5	[kPa]
Circulation pump - Type	external	[-]
Circulation pump - residual head	-	[mWs]
Circulation pump - max. power	-	[W]
Source Side		
Evaporator - Type	Plate heat exchanger	[-]
Evaporator - Material	Stainless steel, copper brazed	[-]
Evaporator - Flowrate (3K)	2,63	[m³/h]
Evaporator - Pressure loss	16,90	[kPa]
Source - Type	external	[-]
Source - residual head	-	[mWs]
Source - max. Power	-	[W]

Performance Data*


Oper. point	Comp. speed	Heating cap.	Cooling cap.	Rated Input	COP
B0/W35	54%	5,8	4,6	1,2	4,74
B0/W35	75%	8,0	6,3	1,7	4,71
B0/W35	100%	10,6	8,2	2,4	4,42
B0/W55	100%	9,0	5,9	3,0	2,95
B0/W35	Minimal	2,8	2,2	0,6	4,59
B0/W55	Minimal	3,5	2,2	1,3	2,76

Clim.: warmer	35°C	SCOP	5,16
		η_s	203
	55°C	SCOP	3,88
		η_s	152
Clim.: average	35°C	SCOP	5,29
		η_s	206
	55°C	SCOP	3,96
		η_s	155
Clim.: colder	35°C	SCOP	5,08
		η_s	200
	55°C	SCOP	4,06
		η_s	159



* Compressive performance deviations of up to 10% are possible. All informations without guarantee: typographical and printing errors reserved.

Operating limit



Connection measurements


Heat Pump Dimensions (H x W x D)

[mm] 1.300 x 600 x 650

Heat Pump Weight

[kg] 162

- A: Source Inlet, G1" AG
- B: Heating Outlet, G1" MT
- C: Source Outlet, G1" AG
- D: Heating Inlet, G1" FT
- E: Electrical Inlet
- F: not in usage
- G: not in usage



Free spaces

- A: 400mm
- B: 400mm
- C: 200mm
- D: 600mm
- E: 400mm

